



Satellite TT



Satellite Eco



Satellite II



Growing Concept



# Jelly Satellite

The 'Jelly Satellite' is the latest addition to Bakon's range of glaze spraying equipment. The Jelly Satellite is characterized by its striking design which takes into account the essential requirements of hygiene regulations, ease of cleaning and ease of use.

The major improvement in this new machine is in the control and operation of the machine. The Jelly Satellite is equipped with a display of four control keys. The display shows the set values for each function and also provides information about the actual spraying pressure and actual temperature of the glaze and the temperature of the heated hose.

## Special features

- Advanced, mobile design
- Easy to operate with a well-organized control panel
- Sprays almost every type of glaze
- The design is developed according to HACCP guide lines
- Movable (with the exception of the TT)
- Easy maintenance and service
- Completely made of stainless steel and other non-rusting materials
- Solid and robust

This machine is available in seven models, as follows -

- Jelly Satellite I > with one spray gun
- Jelly Satellite II > with two spray guns
- Jelly Satellite T > with two spray guns and two separate heating systems
- Jelly Satellite T.P. > suitable for semi-industrial use
- Jelly Satellite H.C. > for spraying hot and cold products
- Jelly Satellite TT > compact, to be placed on the working-table
- Jelly Satellite Eco > simple model with one spray gun

## Technical specifications

Details for all types with the exception of TT and Eco:

- control panel, which can be read digitally
- protection of vital machine components (safety and conservation)
- various function controls in the machine system
- failure reports on the display
- start up and shutting off instructions on the display
- text display readable in various languages
- accurate temperature adjustment
- the temperature of the heated hose is adjustable

	Satellite I	Satellite II	Satellite T	Satellite TP	Satellite HC	Satellite TT	Satellite ECO
<b>Temperature</b>	digital adjustable up to 95°C	digital adjustable up to 95°C	digital adjustable up to 95°C	digital adjustable up to 95°C	digital adjustable up to 95°C	fixed temperature	fixed temperature
<b>Spray pressure</b>	fixed, digitally readable	fixed, digitally readable	adjustable from 0 till 3,4 bar digitally readable	adjustable from 0 till 3,4 bar digitally readable	adjustable from 0 till 3,4 bar digitally readable	fixed spraying pressure	fixed spraying pressure
<b>Number of spray guns</b>	1	2	2	2	2	1	1
<b>Number of heaters</b>	1	1	2	2	1	1	1
<b>Glaze output</b>	600 cc/min	1200 cc/min (600 cc/min per spray gun)	1200 cc/min (600 cc/min per spray gun)	1200 cc/min ( 600 cc/min per spray gun)	600 cc/min	400 cc/min	400 cc/min
<b>Heating power</b>	2500 Watt	2500 Watt	3000 Watt	5000 Watt	2500 Watt	1500 Watt	1500 Watt
<b>Total power</b>	2660 Watt	2720 Watt	3220 Watt	5120 Watt	2620 Watt	1660 Watt	1660 Watt
<b>Voltage</b>	220/240 VAC	220/240 VAC	220/240 VAC	3x400 + N V, 50 Hz	220/240 VAC	110/220/240 VAC	110/220/240 VAC
<b>Adjustable hose temperature</b>	yes	yes	yes	yes	yes	no	no
<b>Own air supply</b>	yes	yes	yes	no	yes	yes	yes
<b>Display</b>	B	B	B	B	B	A	A
<b>Dimensions (dxwxh)</b>	465 x 620 x 1372 mm	465 x 620 x 1372 mm	465 x 620 x 1372 mm	465 x 620 x 1372 mm	465 x 620 x 1372 mm	358 x 440 x 430 mm	465 x 620 x 1372 mm
<b>Weight</b>	74 kg	74 kg	88 kg	88 kg	74 kg	30 kg	72 kg



Controlpanel Type A



Controlpanel Type B